

CCNP 642-832 TSHOOT Ticket 8 – Switchport VLAN 10

In this post; [CCNP 642-832 TSHOOT TROUBLE TICKETS \(TT\) Questions](#), i have introduced the trouble tickets questions of 642-832 exam. And you can reading it carefully, any questions then contact me. Also, i have uploaded the topology. Lab-Sim Topology.pdf Client 1 & 2 are getting 169.x.x.x ip addresses and can't ping DSW1 or FTP Server but they are able to ping each other. Situation: in port channel configuration of ASW1 vlan 10 is not allowed. (Use L2 Diagram) Configuration of ASW1 interface FastEthernet1/0/1 switchport mode access switchport access vlan 1 ! interface FastEthernet1/0/2 switchport mode access switchport access vlan 1 On ASW1, on interfaces fa0/1, fa0/2 switchport access vlan 1 Answer: on ASW1 change **switchport access vlan 1** to **switchport access vlan 10** Ans1)ASW1 Ans2)Vlan Ans3)give command: interface range fa1/0/1-2 & switchport access vlan 10 Situation: Clients are unable to ping DSW1, because their access ports aren't configured for VLAN 10 on ASW1 (both ports are in the default VLAN1). Symptoms:- 1- Clinets are getting 169.x.x.x Ip address. 2- Clinet 1 can ping Client 2 and vice versa. 3- ?sh running-config' command will not display ?switchport access vlan 10? under the interfaces fa1/0/1 and fa1/0/2 .