

## [New Exam Dumps 130q 642-035 Exam Dumps Offered By PassLeader Help Passing Exam Easily

New Updated 642-035 Exam Questions from PassLeader 642-035 pdf dumps! Welcome to download the newest PassLeader 642-035 vce dumps: <http://www.passleader.com/642-035.html> (130 Q&As) Keywords: 642-035 exam dumps, 642-035 exam questions, 642-035 vce dumps, 642-035 pdf dumps, 642-035 practice test, 642-035 study guide, Troubleshooting Cisco Unified Computing (DCUCT) Exam NEW QUESTION 83 Refer to exhibit. A Cisco UCS admin is troubleshooting an issue with a vNIC not coming up on a blade. When looking at the CLI of the "Fabric Interconnect", the admin runs this command to view the status of the interface. Which option describes a possible reason why the interface is stuck in an "initializing" state?

```
aci-sol-calo-ucsb-A(nxos)# sh
Vethernet813 is down (initializing)
  Bound Interface is port-channel
  Port description is server
  Hardware is Virtual, address 10.10.10.10
  Port mode is trunk
  Speed is auto-speed
  Duplex mode is auto
  300 seconds input rate 0 bps
  300 seconds output rate 0 bps
Rx
  0 unicast packets 0 multicast
  115 input packets 32934 bytes
  0 input packet drops
Tx
  0 unicast packets 29 multicast
  29 output packets 8729 bytes
  0 flood packets
  0 output packet drops
```

A. The service profile is not applied to a blade. B. The VLANs defined on the vNIC are not defined on a matching uplink port. C. The uplink port is down. D. The QoS policy on the vNIC is invalid. E. The MTU on the vNIC is higher than the MTU configured in the QoS system class. Answer: C NEW QUESTION 84 Which two options are causes for failure of a Cisco C-Series server that is configured to boot from SAN? (Choose two.) A. The boot LUN ID is not 0. B. The iSCSI target is only available via one path through the network. C. C-Series does not support boot from SAN. D. The KVM dongle is attached to the front of the server with a USB stick installed. E. Under the FCoE properties on the vNIC adapter, the FCoE VLAN ID is set to 10. F. The boot table for fc0 has not been configured. Answer: DF NEW QUESTION 85 Which command on the Fabric Interconnect displays packet statistics for a given QoS group and MTU size? A. show policy-map interface ethernet x/y B. show queuing interface ethernet x/y C. show interface ethernet x/y D. show class-map type qos E. show interface queuing ethernet x/y Answer: B NEW QUESTION 86 A Cisco UCS admin is trying to integrate Cisco UCS Manager with Active Directory Authentication. After the configuration is done, the admin is still unable to log in using LDAP credentials. When running a debug on the Fabric Interconnect, this error is displayed: ldap\_build\_roles\_and\_locales\_from\_attr: No attr for usr profile Which step was missed in the configuration? A. The LDAP provider was not configured correctly. B. The proper RBAC role(s) were not assigned to the user. C. Cisco UCS Manager 2.1 is required for LDAP integration. D. The "Attribute" field in Cisco UCS was left blank. Answer: B NEW QUESTION 87 Which three requirements are needed to configure a blade to boot successfully from Fibre Channel? (Choose three.) A. zoning B. LUN masking C. WWPN device alias D. boot from SAN policy E. SAN connectivity policy F. port assignment G. target WWPN needs to be set in the boot from SAN policy Answer: ABD NEW QUESTION 88 Which description of a core file is true? A. It is generated by a system failure. B. It is generated by a process failure. C. It is generated by a component failure. D. It is generated by a hardware failure. Answer: B NEW QUESTION 89 Which logs are used to troubleshoot hardware failure? A. system event log B. audit log C. accounting log D. gateway logs E. system log Answer: A NEW QUESTION 90 A UCS Admin is trying to launch the KVM console but it is failing to launch. All IP Pools for mgmt are configured and the CIMC has an address in UCSM. They SSH to the fabric Interconnect and run an ethanalyzer while issuing a ping

from their local PC to the KVM IP address. The ping is successful but they do not see the ICMP requests and replies displayed in the capture. Here is the filter they used: `FIA(nxos)# ethalyzer local interface mgmt display-filter icmp limit-captured-frames 0`

What could be the reason pings are not seen in the capture and the KVM is failing to load? A. Java settings are preventing the KVM from loading B. There is a duplicate IP address for that CIMC address

C. The switch upstream from the FI has the wrong vlan configured D. The CIMC IP pool is in the same subnet as the Fabric Interconnects mgmt 0 interface Answer: B

NEW QUESTION 91 Where do you configure users so that they cannot access resources that belong to other organizations? A. roles

B. domain separation C. locals D. VDCs Answer: C

NEW QUESTION 92 What is the correct procedure to change Ethernet switching modes? A. Navigate to the subordinate Fabric Interconnect in the GUI, choose "Set Ethernet Switching mode", wait for it to come back up, and repeat on the primary FI.

B. Navigate to either Fabric Interconnect in the GUI, choose "Set Ethernet Switching mode", and wait while both FIs reboot simultaneously. C. Navigate to either Fabric Interconnect in the GUI and transparently update the mode to switching. Repeat on the other Fabric Interconnect.

D. Simply start using the switching features. The Fabric Interconnect automatically reconfigures to use Ethernet Switching Mode. Answer: B

NEW QUESTION 93 Which power policy should be chosen to maximize the performance of a Cisco UCS system with four PSUs and eight blades? A. non-redundant B. N+1 C. grid

D. performance Answer: C Download the newest PassLeader 642-035 dumps from [passleader.com](http://passleader.com) now! 100% Pass Guarantee! 642-035 pdf dumps & 642-035 vce dumps: <http://www.passleader.com/642-035.html> (130 Q&As)