[Feb-2016 Dumps Professional 234q 642-737 Braindump For Free Download Now

New Updated 642-737 Exam Questions from PassLeader 642-737 PDF dumps! Welcome to download the newest PassLeader 642-737 VCE dumps: **http://www.passleader.com/642-737.html** (234 Q&As) Keywords: 642-737 exam dumps, 642-737 exam questions, 642-737 VCE dumps, 642-737 PDF dumps, 642-737 practice tests, 642-737 study guide, 642-737 braindumps, Implementing Advanced Cisco Unified Wireless Security (IAUWS) Exam **NEW QUESTION 194**   What device will authenticate the user when a sponsor creates a guest account on the Cisco NGS? A.   WLAN controller B.   Cisco ACS   C.   Cisco NGS   D.   active directory server **Answer: C NEW QUESTION 195**   A lobby ambassador is creating guest access accounts. At which two locations can the accounts be stored? (Choose two.) A.   NAC guest server   B.   Active directory C.   WLAN controller   D.   WCS   E.   ACS **Answer: CD NEW QUESTION 196**   An engineer is configuring the guest WLAN to redirect to a created login page uploaded to the controller. Which three CLI commands are required if the guest WLAN is on WLAN 2? (Choose three.) A.   config wlan security web-auth enable 2   B.   config wlan custom-web global enable 2   C.   config wlan custom-web webauth-type customized 2   D.   config wlan custom-web login-page login.html 2 E.   config wlan custom-web webauth-type internal 2   F.   config wlan custom-web login-page customized 2 **Answer: ACD NEW QUESTION 197**   An engineer creating a configuration file to upload to a controller would like the guest WLAN to be set for L3 authentication only. What command must be included in the configuration file? A.   config wlan security web-auth enable 2   B.   config wlan security wpa wpa2 disable 2   C.   config wlan security web-auth server-precedence 2 local radius ldap D.   config wlan custom-web global enable 2 **Answer: A NEW QUESTION 198**   An engineer is configuring the anchor controller for a guest network. What setting in the guest WLAN can be different from the foreign controllers? A.   VLAN   B.   radio policy   C.   QOS setting D.   WLAN advanced settings **Answer: A NEW QUESTION 199**   All users on one of the two guest WLANs are failing to connect after a configuration change was made to a controller. What is the cause of the outage? A.   The interface or VLAN of the anchor controller and foreign controller no longer match. B.   The configuration of the failing WLAN no longer matches the foreign controllers. C.   The address of the NAC guest server has been changed.   D.   The DHCP server on the foreign controller was changed. **Answer: B NEW QUESTION 200**   What three items can be found on the Wireless Control System PCI DSS Compliance Report? (Choose three.) A.   all authentication and encryption violations B.   all ACL violations and reports   C.   all IDS threats   D.   detailed association history for clients connected to the network   E.   all SSIDs not using Client Exclusion F.   all access points that have rogue detection enabled **Answer: ACD NEW QUESTION 201**   An engineer is segmenting WLAN traffic by security options after the client has received an IP address. Which two security options are possible? (Choose two.) A.   web policy   B.   Cisco Key Integrity Protocol C.   PSK   D.   802.1x   E.   VPN pass-through **Answer: AE NEW QUESTION 202**   An engineer is configuring 802.1x authentication on an autonomous AP. What two configuration commands must be included on the AP if the RADIUS server IP is 10.9.4.9? (Choose two.) A.   radius-server host 10.9.4.9 auth-port 1812 acct-port 1813 key Cisco123   B.   aaa new-model   C.   aaa authorization   D.   aaa attribute list 10.9.4.9   E.   aaa group server radius 10.9.4.9 **Answer: AB NEW QUESTION 203**   An engineer has configured passive fallback mode for RADIUS with default timer settings. What will occur when the primary RADIUS fails then recovers? A.   RADIUS requests will be sent to the secondary RADIUS server until the secondary fails to respond.   B.   The controller will immediately revert back after it receives a RADIUS probe from the primary server.   C.   After the inactive time expires the controller will send RADIUS to the primary.   D.   Once RADIUS probe messages determine the primary controller is active the controller will revert back to the primary RADIUS. **Answer: C NEW QUESTION 204**   What is the default SYSLOG level in a wireless LAN controller? A.   alert   B.   notification C.   error   D.   informational   E.   debugging **Answer: C NEW QUESTION 205**   An engineer is configuring IDS signatures and sets Bcast deauth to enabled and immediately begins to see

Broadcast deauthentication frame alerts. What Cisco recommended solution would resolve this issue? A.   disable Bcast deauth   B.   disable Broadcast SSID on the WLAN   C.   enable MFP on the WLAN   D.   locate and disable the attacker **Answer: C NEW QUESTION 206**   Client adapters on the wireless network are locking up and a packet capture shows many management frames with no SSID element. What signature should the engineer enable for the WLC to report this issue in the future? A.   Deauth flood B.   Null probe resp 2   C.   EAPOL flood   D.   Wellenreiter **Answer: B NEW QUESTION 207**   The controller is reporting an IDS signature 'deauth flood' attack and it has been determined that the default settings are too sensitive for the environment. What signature details should be adjusted to only trigger the alert on a certain amount of client packets within a certain period of time? A.   Measurement Interval and Quiet Time B.   Signature Frequency and Signature MAC Frequency   C.   Measurement Interval and Signature MAC Frequency   D.   Quiet Time and Signature Frequency **Answer: C NEW QUESTION 208** When creating a custom rogue classification, what three conditions would be added to alert on a specific internal SSID with more than 5 clients at -80db? (Choose three.) A.   SSID   B.   RSSI   C.   SNR   D.   duration   E.   client-count   F.   managed-ssid **Answer: BEF NEW QUESTION 209**   Many users report being disconnected from the WLAN and WCS shows events for broadcast deauthentication frames. What security feature mitigates the issue? A.   WPA2 B.   MFP   C.   IDS   D.   ACL   E.   IPS **Answer: B NEW QUESTION 210**   ......   Download the newest PassLeader 642-737 dumps from passleader.com now! 100% Pass Guarantee! 642-737 PDF dumps & 642-737 VCE dumps: **http://www.passleader.com/642-737.html** (234 Q&As)